

Shown with optional Stone & Twig Kit

Elevated Elegance

The mid-sized ProBuilder™ 54 Linear features sleek, elegant styling and a contemporary fire viewing area that showcases tall dancing flames. This fireplace is designed to provide comforting radiant heat plus excellent natural convection to homes and living spaces up to 1,650 square feet.



ProBuilder Series[™] 54 Linear Gas Fireplace



FEATURES YOU'RE GOING TO LOVE

- · Available in two models:
- Standing Pilot Millivolt (No electrical hookup required).
- GreenSmart® Basic 2 (GSB2). featuring GreenSmart Pilot (Requires electrical hook-up)
- 54" W x 15" T tempered glass viewing area.
- · Glass barrier screen is flush to wall.
- · Easy access gas controls.
- Sleek linear style with beautiful flame presentation.
- · Heavy gauge 16-18 steel construction.
- · Can operate in a power outage.

OPTIONS




- · Wall mounted GreenSmart® Basic Remote
- 180 CFM Convection Fan
- Black Glass Fireback
- Underlit Accent Lights
- Multiple media options: Colored Glass, Stones and Twigs/Classic Logs
- The CoolSmart[™] Wall transfers heat to a vent near the ceiling, allowing you to safely add a television above the fireplace.

SPECIFICATIONS

- · Heating Capacity*: Up to 1,650 Sq. Ft.
- Maximum BTU Input (NG/LP):
 33,000 Per Hour with 50% turndown.
- P4 Efficiency: GSB2 65.9% (NG) 67% (LP)
 MV 65.1% (NG) 66.3% (LP)
- · Weight: 165lbs. (75kg).
- *Heating capacity will vary with floor plan, Insulation, and outside temperature.


DIMENSIONS




INSTALLATION

Clearances

- (A) To Side of Fireplace 1/2" (13mm).
- (B) To Back of Fireplace 1/2" (13mm).
- (C) 0" clearance to combustible side facing or walls.



Minimum Framing







www.fireplacex.com