CUTOUT DIMENSIONS

COUNTERTOP NOTCH REQUIREMENT

*Add 3.25" to allow for hood opening



Allow minimum of 2.50" clearance from the grill's rear edge and 3.25" from cutout to the backsplash to allow hood to fully open.



INSULATING JACKETS						
MODEL NUMBER	OVERALL DIMENSIONS			CUTOUT DIMENSIONS		
	A WIDTH	B DEPTH	C HEIGHT	D WIDTH	E DEPTH	F HEIGHT
TEIJ24	28-5/8"	23-7/16"	13"	26-7/8"	22-1/4"	12-5/8"
TEIJ30	34-3/4"	27-1/8"	13-1/4"	33-1/2"	26"	12-5/8"
TEIJ36	40-3/4"	27-1/8"	13-1/4"	39-1/2"	26"	12-5/8"
TEIJ42	46-3/4"	27-1/8"	13-1/4"	45-1/2"	26"	12-5/8"
TEIJ54	58-3/4"	27-1/8"	13-1/4"	57-1/2"	26"	12-5/8"

TEIJ: Insulating jackets for installation in combustible construction



ACCESS DOOR DIMENSIONS				
MODEL NUMBER	OVERALL DIMENSIONS		CUTOUT DIMENSIONS	
	H WIDTH	I HEIGHT	J WIDTH	K HEIGHT
TEAD18(R/L)-C	18"	20-3/4"	16-1/4"	19"
TEAD24(R/L)-C	24"	20-3/4"	22-1/4"	19"
TEAD30-C	30"	20-3/4"	28-1/4"	19"
TEAD36-C	36"	20-3/4"	34-1/4"	19"
TEAD42-C	42"	20-3/4"	40-1/4"	19"

Twin Eagles reserves the right to change the specifications, designs and materials of the products without notice.
Please verify the specifications prior to finalizing your enclosures.